

CLASSIC LINE

# ARMONIA

Washable water-based matt paint

CODE 00-700

## DESCRIPTION AND USE

Washable water-based paint for interiors and exteriors with a vinyl resin base, particularly indicated for the protection and decoration of wall surfaces (new or previously painted). Its main features are ease of application, high coverage, excellent hiding power thanks to its measured opacity, expansion and open time.

Aspect of the dry film: flat

**Washable with a damp sponge after at least 15 days from the last application.**

## APPLICATION DATA

<b>1 h</b> DRY TO TOUCH	<b>6 h</b> RECOAT TIME	<b>8 m<sup>2</sup>/l</b> SPREAD RATE 2 coats	 40% v/v STANDARD FINISH	 60% v/v LACQUER FINISH	 30% v/v	
-------------------------------	------------------------------	--	--	--	--	---

## TECHNICAL DATA

<b>COMPOSITION</b>	Vinyl-versatate copolymer in water dispersion, titanium dioxide, selected charges and special additives
<b>SPECIFIC GRAVITY</b>	1.540±0.020 Kg/L
<b>FLASH POINT</b>	Not flammable
<b>SOLIDS BY VOLUME</b>	40%
<b>V.O.C.</b>	< 30 g/L
<b>AVERAGE VISCOSITY</b>	(Brookfield rot. No.4/2 rpm at 21°C): 400 Poises
<b>FILM THICKNESS</b>	Dry: 150 Wet: 60 per coat (µm)
<b>FINENESS OF GRIND</b>	40 (µm)
<b>COLOURS</b>	White
<b>PACKAGING</b>	4000 ml – 10000 ml – 14000 ml

Revision No. 0 dated February 2009

**WARNINGS:**

- Keep from freezing.
- Clean the tools with water immediately after use.
- Store in a cool, dry place away from direct sunlight

**APPLICATION GUIDE**

Surface must be clean and dry.

- **New walls:** apply one coat of Fissativo Acrilico (thinned 1:7 with water). Wait at least 4 hours before applying two coats of Armonia.
- **Walls already painted:**
  - With washable water-based paints: fill holes with plaster and sand if necessary; clean the surface with a damp sponge and apply one coat of Fissativo Acrilico (thinned 1:7 with water), only over patched areas. Wait at least 4 hours and apply two coats of Armonia.
  - With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary; clean the surface with a damp sponge and apply one coat of Fissativo Acrilico (thinned 1:6 with water) over the whole surface. Wait at least 4 hours before applying the successive two coats of Armonia.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.