

DECORATIVE LINE

ATMOSFERE

Decorative finish


CODE 18-4...

DESCRIPTION AND USE

Not yellowing acrylic resin-based finish; thanks to its peculiar structure and composition and according to the thinning and working tools used for the application, it can create the most different decorative effects. Atmosfere is the perfect ally for both professional decorators and Do-It-Yourself lovers; its varying shades, deep nuances, transparencies and contrasts will give an exceptional aspect to your decorations. The final result will be a soft, harmonious, fascinating and enthralling *atmosphere*.

Washable after complete desiccation: wait at least 15 days from the last application.

Aspect of the dry film: polished, flat and waxed

APPLICATION DATA**TECHNICAL DATA**

COMPOSITION	Pure acrylics copolymer-based, with structuring agents and specific additives
SPECIFIC GRAVITY	1.030±0.030 g/L
FLASHPOINT	Not flammable
SOLIDS BY VOLUME	15%
AVERAGE VISCOSITY	(Brookfield rot. No. 5 at 20rpm): 12000 Cps ±0.500 at 21°C
FILM THICKNESS	Dry: 15 – Wet: 100 (µm)
COLOURS	See colour card
PACKAGING	2500 ml – 1000 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation

Revision No. 3 dated 16/05/2006

PAINT SYSTEM

• **New walls:** apply one brush coat of Fissativo Acrilico (thinned 1:7 with water). Wait at least 4 hours and apply Vogue for smooth finish or Rustico Provenzale for “antique effect” finish (see technical data sheets for application).

• **Walls already painted:**

- **With washable water-based paint:** fill holes with plaster and sand if necessary; clean with a damp sponge and apply one brush coat of Fissativo Acrilico (thinned 1:7 with water) only over patched areas. After at least 4 hours apply Vogue for smooth finish or Rustico Provenzale for “antique effect” finish (see technical data sheets for application).

- **With distemper, lime paint and chalky paint:** fill holes with plaster and sand if necessary; clean with a damp sponge and apply one brush coat of Fissativo Acrilico (thinned 1:6 with water) over the whole surface. After at least 4 hours apply Vogue for smooth finish or Rustico Provenzale for “Antique effect” finish. (See technical data sheets for application)

APPLICATION:

“Subtractive” finish:

- STEP 1 Prepare the surface as described in the paint system.
- STEP 2 Apply Atmosfere with a flat brush or wool paint roller over about 1 sqm of the surface.
- STEP 3 Tools chosen for final decoration (pad, sponge, cloth, glove, comb, paint roller, spatula) must be used immediately, when the product is still wet.
NB: keep always an irregular area of 4-5 cm of product not subjected to final decoration: this will help you connect to the following working area. The finish obtained with this technique will be more intense than the finished obtained with the additive method.

“Additive” finish:

- STEP 1 Prepare the surface as described in the paint system.
- STEP 2 Thin Atmosfere to 20% v/v with water; dip the tool chosen for final decoration (pad, sponge, cloth, glove) into the product and blot to obtain more consistent finish.
N.B. In order to avoid joints of different colours, do not apply the product over those areas where it has already dried. The finish obtained with this technique will be less intense than the finished obtained with the subtractive method.

“Glazing” finish:

- STEP 1 Prepare the surface as described in the paint system.
- STEP 2 Thin Atmosfere to 50% with water; dip the tool chosen for final decoration (brush, cloth, glove) into the product.
N.B. In order to avoid joints of different colours, do not apply the product over those areas where it has already dried.