

PROFESSIONAL LINE

# CAPSULA PRIMER

Anti-fungal consolidating primer for the encapsulation of asbestos cement surfaces  
**CODE 44-100**

**DESCRIPTION AND USE**

Anti-fungal consolidating primer for the encapsulation (inertisation) of asbestos cement surfaces such as old coverings, false ceilings or handworks.  
Film aspect (dry): transparent light blue

**APPLICATION DATA**

|                            |                            |   |  |  |   |  |
|----------------------------|----------------------------|---|--|--|---|--|
| <b>1 h</b><br>DRY TO TOUCH | <b>12 h</b><br>RECOAT TIME | <b>5 m<sup>2</sup>/l</b><br>SPREAD RATE |  |  | <br>conventional | <b>AIRLESS</b><br>Ø 0.015"-0.021"<br>pressure: 150 atm |
|----------------------------|----------------------------|---|--|--|---|--|

**TECHNICAL DATA**

|                          |  |
|--------------------------|--|
| <b>COMPOSITION</b>       | Vinyl-versatate resins in water dispersion and special additives                       |
| <b>SPECIFIC GRAVITY</b>  | 1.000 g/L  |
| <b>FLASH POINT</b>       | Not flammable  |
| <b>SOLIDS BY VOLUME</b>  | 12%  |
| <b>V.O.C.</b>            | < 30 g/L   |
| <b>AVERAGE VISCOSITY</b> | (Ford no. 4 Cup at 21°C): 12Sec  |
| <b>PACKAGING</b>         | 20000 ml – 5000 ml   |
| <b>STORAGE</b>           | Keep from freezing. Keep in a cool and dry place. Do not apply below 5°C or over 35°C. |

This product is supplied with a certificate of conformity released by Istituto Politecnico Giordano  
No. 138687 dated 07/07/2000.

Revision No. 2 dated February 2009

## **PAINT SYSTEM**

Shake well before use.

Use a high-pressure washer or broomcorn brush to remove all dirt, grease, moss and lichens normally present on old roofings.

Wet clean the surface and constantly damp in order to avoid air dispersion of asbestos fibres. We suggest filtering washwater and collect fibre wastes to dispose of in special dumps.

- Fastener pivots of asbestos-cement plates: we suggest brushing and applying one thick coat of Fergum HB anti-rust.

- How to repair cracks and holes with 2-pack Lightweight Filler.

When the surfaces previously prepared are fully dry apply one coat of Capsula Primer.

For not very absorbent surfaces, the product must be thinned 2:1 with water.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.