

CASAVIVA DETERGENTE

Anti-mould coating

CODE 13-600

DESCRIPTION AND USE

Excellent solution used to effectively remove moulds and spores from wall surfaces. It can be applied over interior and exterior walls contaminated with all kinds of molds.

APPLICATION DATA**TECHNICAL DATA**

COMPOSITION	Anti-bacteria agents dissolved in aqueous alcohol solution
SPECIFIC GRAVITY	0.980 ± 0.050 kg/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	2%
AVERAGE VISCOSITY	Aqueous fluid
PACKAGING	1000 ml
STORAGE	Store in a dry place with adequate ventilation at room temperature

APPLICATION GUIDE

- **Interior walls:** apply the solution without brushing walls in order to avoid spreading spores in the surrounding area. Let the surface dry for 5 hours. If moulds are particularly difficult to remove, apply a second coat. Brush carefully to remove moulds.

Finally, apply Casaviva Anticondensa, Action or other traditional water-based paints additivated with Casaviva Additivo.

- **Exterior walls:** Carefully brush contaminated surfaces. Apply one roll or brush coat of Casaviva Detergente. Let the surface dry for at least 5 hours. If moulds are particularly difficult to remove, apply more coats of products. Apply our Rivestimenti per esterno (exterior coating) additivated with Casavivo Additivo.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.