

CLASSIC LINE

FACILE

Breathable acrylic water-based paint

CODE 109-9..

DESCRIPTION AND USE

Interior and exterior breathable acrylic water-based paint designed for protection and decoration of all kinds of wall surfaces. It is particularly indicated for application in humid places or where previous coatings do not show strong adherence.

Aspect of the dry film: flat

APPLICATION DATA

1 h DRY TO TOUCH

4 h

7 m²/t SPREAD RATE 2 COATS







TECHNICAL DATA

COMPOSITION	· · · · · · · · · · · · · · · · · · ·
	titanium dioxide, slected charges and water-
4.7	resistant extenders
SPECIFIC GRAVITY	1.600 ± 0.030 Kg/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	40%
V.O.C.	< 30 g/L
AVERAGE VISCOSITY	400 Poises (Brookfield rot. No. 4 at 2rpm at 21℃)
FLM THICKNESS	Dry: 70 – Wet: 160 2 coats (μm)
FINENESS OF GRIND	20 microns
COLOURS	White - Tingo - Selezione Interni
PACKAGING	14000 ml-10000 ml - 4000 ml - 2500 ml - 750 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation





APPLICATION GUIDE

The surface must be clean and dry.

- New walls: apply one brush coat of Supernovità. Wait at least 4 hours then apply two more coats of Facile.
- Walls already painted:
- With washable water-based paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge then apply one brush coat of Supernovità, only over patched areas. Wait at least 4 hours and apply 2 more coats of Facile.
- With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary;
 clean the wall with a damp sponge then apply one brush coat of Supernovità over the whole surface. After min. 4 hours apply two more coats of Facile.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself