

CLASSIC LINE

FAX

Breathable water-based paint




CODE 09-2..

DESCRIPTION AND USE

Breathable acrylic water-based paint for interiors. Its main features are excellent coverage, filling properties and ease of application. It is particularly indicated for application on ceilings and walls where adherence and breathability are required.

Aspect of the dry film: flat

APPLICATION DATA

| | | | | | |
|----------------------------|---------------------------|--|---|--|--|
| 1 h DRY TO TOUCH | 4 h RECOAT TIME | 5 m²/l SPREAD RATE 2 COATS |  30% v/v |  40-50%v/v |  |
|----------------------------|---------------------------|--|---|--|--|

TECHNICAL DATA

| | |
|--------------------------|---|
| COMPOSITION | Acrylic copolymers in water dispersion, titanium dioxide, selected charges and extenders. |
| SPECIFIC GRAVITY | 1.700 ± 0.030 Kg/L |
| FLASH POINT | Not flammable |
| SOLIDS BY VOLUME | 50% |
| V.O.C. | < 30 g/L |
| AVERAGE VISCOSITY | 450 Poises (Brookfield rot. No. 4 at 2rpm at 21 °C) |
| FILM THICKNESS | Dry: 70 – Wet: 160 two coats (µm) |
| COLOURS | White – Tingo – Selezione Interni |
| PACKAGING | 14000 ml – 4000 ml |
| STORAGE | Keep from freezing. Store in a cool, dry place with adequate ventilation. |

Revision No. 3 dated 07/07/2003

APPLICATION GUIDE

Surface must be clean and dry.

- **New walls:** apply one brush coat of Supernovità. Wait at least 4 hours then apply 2 coats of Fax.
- **Walls already painted:**
 - With washable water-based paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours then apply two coats of Fax
 - With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità over the whole surface. Wait at least 4 hours then apply two coats of Fax.