

PROFESSIONAL LINE

FISSATIVO ACRILICO

Interior and exterior penetrating primer



CODE 13-094

DESCRIPTION AND USE

Consolidating alkali-resistant and high-penetrating primer for exteriors and interiors; it is recommended for all kinds of masonry surfaces such as plaster, plasterboard, lime trimming, civil plaster based on lime and/or cement, quartz based paints, silicates, siloxane and lime; it reduces and levels surface absorption, allowing perfect anchoring and giving a uniform aspect to the topcoat.

Aspect of the dry film: transparent

APPLICATION DATA

½h DRY TO TOUCH	12h EXTERIOR 4h INTERIOR RECOAT TIME	25 m²/l exterior 50 m²/l INTERIOR SPREAD RATE		 THINNING 400% OUTDOOR 800% INDOOR
---------------------------	--------------------------------------------------------------	--------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------

TECHNICAL DATA

COMPOSITION	Acrylic copolymers in water dispersion and selected additives
SPECIFIC GRAVITY	1.050±0.010 g/L
AVERAGE VISCOSITY	20 Sec (Cup no. 8 at 21°C)
SOLIDS BY VOLUME	40%
V.O.C.	< 30 g/L
FLASH POINT	Not flammable
PACKAGING	20000 ml – 5000 ml – 1000 ml

Revision No. 0 dated February 2009

WARNINGS:

- Keep from freezing
- Shake well before and during use
- Do not apply in direct sunlight and when temperature is below 5°C and over 35°
- Clean the tools with water after use
- Store in a cool, dry place away from sunlight

PAINT SYSTEM:

Apply on dry and solid surface, removing all dust.

EXTERIORS: THINNING 400%

New Walls: When plaster is completely dry (at least 30/40 days), apply one brush coat of FISSATIVO ACRILICO.

Painted walls:

- Unpainted degraded walls: thoroughly brush with a wire brush; clean the surface with low pressure hydro-cleaner and let it dry. Apply one brush coat of FISSATIVO ACRILICO.
- Walls with old paint and loose: remove all loose paint and plaster; brush with a wire brush. Clean with a low pressure hydro-cleaner and let the surface dry. Restore all removed areas with hydraulic mortar or ready-miX. Let the surface dry for at least 10 days. Apply one brush coat of FISSATIVO ACRILICO only over restored areas.

INTERIORS: THINNING 800%

New walls: Apply one brush coat of FISSATIVO ACRILICO.

Painted walls:

- With washable water-based paint: fill and sand if necessary; clean the wall with a damp sponge and apply one brush coat of FISSATIVO ACRILICO only over patched areas.
- With distemper, lime paint or chalky paint: fill and sand if necessary; clean the wall with a damp sponge, then apply one brush coat of FISSATIVO ACRILICO over the whole surface.

Orazio Brignola S.p.A. reserves the right to update the above data which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.