

CLASSIC LINE

FLY




Interior wall paint

CODE 209-300

DESCRIPTION AND USE

Breathable water-based paint characterized by ease of application and good coverage, suitable for application on walls and ceilings where adherence and breathability are necessary.
Aspect of the dry film: flat

APPLICATION DATA

1 h DRY TO TOUCH	4 h RECOAT TIME	5 m²/lt SPREAD RATE 2 COATS	 30% v/v	 40-50%v/v	
----------------------------	---------------------------	---	---	---	--

TECHNICAL DATA

COMPOSITION	Based on vinyl-acrylic copolymers in water dispersion, titanium dioxide, charges and extenders.
SPECIFIC GRAVITY	1.720 ± 0.030 Kg/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	51%
V.O.C	< 30 g/L
AVERAGE VISCOSITY	430 Poises (Brookfield rot. No. 4 at 2rpm a 21°C)
FILM THICKNESS	Dry: 50 – Wet: 100 2 coats (µm)
FINENESS OF GRIND	30 µm
COLOURS	White
PACKAGING	14000 ml – 4000 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation.

Revision No. 2 dated February 2009

APPLICATION GUIDE

Surface must be clean and dry.

- **New walls:** apply one coat of Supernovità. Wait at least 4 hours then apply two coats of Fly.
- **Walls already painted:**
 - With washable water-based paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours then apply two coats of Fly.
 - With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary, apply one brush coat of Supernovità over the whole surface. Wait at least 4 hours then apply two coats of Fly.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.
If products are not used beyond our control our liability is limited to the quality of the product itself