

IDROREPELENTE AI SILICONI

CODE 10-080





DESCRIPTION AND USE

Painting product based on silicones dissolved in solvent, providing an hydrorepellent surface without altering its final aspect.

Designed to provide hydrorepellence to cement agglomerates, bricks and masonry in general.

Aspect of the dry film: transparent

APPLICATION DATA



TECHNICAL DATA

COMPOSITION	Based on organosiloxane polymers in solvent
SPECIFIC GRAVITY	0.790±0.050 g/L
FLASH POINT	Over 21°C
SOLIDS BY VOLUME	6%
AVERAGE VISCOSITY	(Ford Cup no. 4 at 21°C): 0.3 Poises
COLOUR	Transparent
PACKAGING	20000 ml – 5000 ml
STORAGE	Store in a cool, dry place with adequate ventilation and at room temperature

PAINT SYSTEM

Surface must be clean and dry to achieve an adequate penetration. Apply in large quantities so that the product can drip over the wall and penetrate into the surface. Repeat until the surface is saturated.

SPECIFICATION ITEM:

IDROPELENTE AI SILICONI

Apply several coats of IDROPELENTE AI SILICONI in large quantities, over clean and dry surface with a spread rate of 0.350 – 1.00 lt/m²

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.