

PROFESSIONAL LINE

**ISOFLEX**

Solvent based pigmented fixative



CODE 13-1..

**DESCRIPTION AND USE**

Exterior pigmented fixative, particularly suitable to consolidate old plasters and concrete. It will even up substrate absorbencies and improve the adherence of the subsequent coats.

Aspect of the dry film: matte

**APPLICATION DATA**

<b>2h</b> DRY TO TOUCH	<b>24 h</b> RECOAT TIME	<b>10m<sup>2</sup>/l</b> SPREAD RATE	 20% v/v Thinner No.7	
---------------------------	----------------------------	---	--	---

**TECHNICAL DATA**

<b>COMPOSITION</b>	Based on vinyl-acetate copolymers with maleic esters dissolved in solution, selected pigments and extenders
<b>SPECIFIC GRAVITY</b>	1.450±0.030 Kg/L
<b>FLASH POINT</b>	over 21°C
<b>SOLIDS BY VOLUME</b>	43.5%
<b>V.O.C.</b>	< 750 g/L
<b>AVERAGE VISCOSITY</b>	(Ford Cup no. 4 at 21°C): 150 sec
<b>PACKAGING</b>	20000 ml
<b>STORAGE</b>	Keep from freezing. Store in a dry and cool place.

Revision No. 0 dated February 2009

## **PAINT SYSTEM**

- **New walls:** brush and apply one coat of Isoflex.
- **Walls to repaint:** remove all old flaky paint, brush energetically to remove any traces of previous coatings and apply one coat of Isoflex.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.  
If products are not used beyond our control our liability is limited to the quality of the product itself.