

**CLASSIC LINE** 

# **MITHOS**

High covering acrylic water paint

**CODE 08-1..** 

## **DESCRIPTION AND USE**

Acrylic water based paint with excellent covering ability. Its formula contains special copolymers helping the formation of the film, without any film forming agents (coalesant) and plastifiers. It is particularly suitable to decorate interiors giving the surface fine satin finishing. Being almost completely free of dangerous substances it may be classified as "low V.O.C. product" and environmentally friendly product.

Easy to apply and easy to wash, it can be used for both interiors and exteriors. Aspect of the dry film: satin

## **APPLICATION DATA**

1h DRY TO TOUCH

6h RECOAT TIME 8 m²/l TWO COATS trimmed surface







## **TECHNICAL DATA**

| COMPOSITION       | based on energial complex maluments in water   |
|-------------------|--|
| COMPOSITION       | The second of th |
|                   | dispersion, titanium dioxide and extenders   |
| SPECIFIC GRAVITY  | 1.530±0.030 Kg/L   |
| FLASH POINT       | Not flammable  |
| SOLIDS BY VOLUME  | 38%  |
| V.O.C.            | < 30 g/L   |
| AVERAGE VISCOSITY | (Brookfield rot. n <sup>o</sup> 4 a 2rpm a 21 <sup>o</sup> C): 315 Poises  |
| FILM THICKNESS    | Dry: 45 – wet: 120 two coats (µm)  |
| FINENESS OF GRIND | 15 microns   |
| COLOURS           | White – TINGO – Selezione Interni  |
| PACKAGING         | 14000 ml – 4000 ml   |
| STORAGE           | Keep from freezing. Store in a cool, dry place with  |
|                   | adequate ventilation.  |

Revision No. 0 dated February 2009





## **WARNINGS:**

- Keep from freezing
- Clean the tools with water after use
- Store in a dry place away from sunlight

## **APPLICATION GUIDE:**

Surface must be clean and dry

 New walls: apply one brush coat of Supernovità. Wait at least 4 hours and apply two coats of Mithos.

## Walls already painted:

- With washable water paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours and apply two coats of Mithos.
- With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary;
  clean the wall with a damp sponge and apply one brush coat of Supernovità over the whole surface. Wait at least 4 hours and apply two coats of Mithos.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.