

CLASSIC LINE

# NELSON BRILLANTE

High coverage quality enamel



CODE 03-3..

**DESCRIPTION AND USE**

High quality gloss enamel, based on special elements providing excellent shine and color retention to the product. Its main feature is the excellent resistance to atmospheric agents especially in marine environment. It can be used over all kinds of surfaces both for interiors and exteriors ensuring perfect and durable protection.

Aspect of the dry film: gloss

**APPLICATION DATA**

<b>2 h</b> DRY TO TOUCH	<b>18h</b> RECOAT TIME	<b>10m<sup>2</sup>/l</b> SPREAD RATE	 READY TO USE	 READY TO USE
----------------------------	---------------------------	---	---	---

**TECHNICAL DATA**

<b>COMPOSITION</b>	Based on alkyd resins, titanium dioxide and light resistant pigments.
<b>SPECIFIC GRAVITY</b>	1.210 ± 0.030 Kg/L
<b>FLASH POINT</b>	Over 21 °C
<b>SOLIDS BY VOLUME</b>	58%
<b>V.O.C.</b>	390 g/L
<b>AVERAGE VISCOSITY</b>	24 Sec (Ford Cup no. 4 at 21 °C)
<b>FILM THICKNESS</b>	Dry: 40 Wet: 70 (µm)
<b>FINENESS OF GRIND</b>	5 microns
<b>COLOURS</b>	Colour card – Tingo
<b>PACKAGING</b>	2500 ml – 750 ml – 375 ml
<b>STORAGE</b>	Keep from freezing. Store in a cool, dry place with adequate ventilation.

## **APPLICATION GUIDE**

Thoroughly clean the surface removing all oil, dirt, flaky paint and rust. Fill holes with plaster and sand if necessary.

Prime the surface with appropriate primers; anti-rust primer for iron, matt primer for wood, Zincogum Plus for glassfibers reinforced plastic, light alloys, copper, stainless steel, PVC and so on.

Apply at least two coats of Nelson Brillante.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.  
If products are not used beyond our control our liability is limited to the quality of the product itself