

CLASSIC LINE

# NELSON SATINATO

Interior and exterior matte enamel



CODE 104-4..

**DESCRIPTION AND USE**

Special matt enamel for interiors and exteriors. Its main features are excellent filling properties, silky uniform and velvety finish for a perfect lacquering and protection of all kinds of surfaces. Excellent yellowing resistance.

Aspect of the dry film: satin

**APPLICATION DATA**

<b>2 h</b> DRY TO TOUCH	<b>18h</b> RECOAT TIME	<b>10m<sup>2</sup>/l</b> SPREAD RATE	 READY TO USE	 READY TO USE
----------------------------	---------------------------	---	---	---

**TECHNICAL DATA**

<b>COMPOSITION</b>	Based on modified alkyd resins, titanium dioxide, selected pigments and special flattening additives.
<b>SPECIFIC GRAVITY</b>	1.200 ± 0.030 Kg/L
<b>FLASH POINT</b>	Over 21°C
<b>SOLIDS BY VOLUME</b>	57%
<b>V.O.C.</b>	398 g/L
<b>AVERAGE VISCOSITY</b>	18 Sec (Ford Cup No. 4 at 21°C)
<b>FILM THICKNESS</b>	Dry: 40 Wet: 70 (µm)
<b>FINENESS OF GRIND</b>	2 microns
<b>COLOURS</b>	Colour card – Tingo
<b>PACKAGING</b>	4000 ml – 2500 ml – 750 ml – 375 ml
<b>STORAGE</b>	Keep from freezing. Store in a cool, dry place with adequate ventilation.

## **APPLICATION GUIDE**

Thoroughly clean the surface removing all oil, dirt, flaky paint and rust. Fill holes with plaster and sand if necessary.

Prime the surface with appropriate primers: anti-rust primer for iron, matt primer for wood, Zincogum Plus for glassfibers reinforced plastic, light alloys, copper, stainless steel, PVC etc. Apply at least two coats of Nelson Satinato.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself