CLASSIC LINE



Washable flat paint

CODE 08-700

DESCRIPTION AND USE

Washable vinyl-based water paint particularly suitable to protect and decorate all kinds of wall surfaces new or previously painted. Its main features ease of application, good coverage (wet and dry), excellent expansion and open time. Aspect of the dry film: flat

APPLICATION DATA



TECHNICAL DATA

COMPOSITION	based on vinyl-versatate copolymer in water
	dispersion, titanium dioxide, charges and selected
	additivies
SPECIFIC GRAVITY	1.560 ± 0.030 kg/L
FLASH POINT	not flammable
SOLIDS BY VOLUME	40 %
V.O.C.	< 30 g/l
AVERAGE VISCOSITY	400 Poises (Brookfield rot. no.4 / 2 rpm at 21°C)
FILM THICKNESS	Wet: 125 Dry: 50 (µm) (per coat)
FINENESS OF GRIND	5 (μm)
COLOURS	White
PACKAGING	4000 - 14000 ml



Revision No. 0 dated February 2009



WARNINGS:

- Keep from freezing
- Clean the tools with water after use
- Store in a dry place away from sunlight

INSTRUCTION FOR USE

Surface must be clean and dry.

• **New walls:** apply one brush coat of Supernovità. Wait at least 4 hours and apply two coats of Perfetta, After min. 4 hours apply two coats of Perfetta.

• Walls already painted

- With washable water paint: fill holes with plaster and sand if necessary; clean with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours and apply two coats of Perfetta.
- With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge, apply one brush coat of Supernovità over the whole surface. Wait at least 4 hours and apply two coats of Perfetta.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.