

PROFESSIONAL LINE

# PERFORMA FONDO

Anti-saltpetre primer  
based on siloxane resin  
**CODE 46-510**

## DESCRIPTION AND USE

Anti-saltpetre primer based on siloxane resin in water dispersion, with high penetrating properties.

It reduces and levels substrate absorbencies and provides hydrorepellence.

It can be applied over the most common surfaces such as civil plasters, lime paints, silicate paints and coatings based on organic binders.

Aspect of the dry film: satin colorless

## APPLICATION DATA

|                            |                            |   |              |   |  |   |
|----------------------------|----------------------------|---|--------------|---|--|---|
| <b>2 h</b><br>DRY TO TOUCH | <b>12 h</b><br>RECOAT TIME | <b>5 m<sup>2</sup>/l</b><br>SPREAD RATE | READY TO USE |  |  |  |
|----------------------------|----------------------------|---|--------------|---|--|---|

## TECHNICAL DATA

|                          |  |
|--------------------------|--|
| <b>COMPOSITION</b>       | Siloxane polymers in water dispersion                          |
| <b>SPECIFIC GRAVITY</b>  | 1.010 ± 0.005 kg/L   |
| <b>FLASH POINT</b>       | Not flammable  |
| <b>SOLIDS BY VOLUME</b>  | 10%  |
| <b>AVERAGE VISCOSITY</b> | 15 Sec (Ford Cup no. 4 at 21°C)                                |
| <b>FILM THICKNESS</b>    | Dry: - Wet: - (µm)   |
| <b>FINENESS OF GRIND</b> | 0.1 µm   |
| <b>COLOURS</b>           | Colorless  |
| <b>PACKAGING</b>         | 20000 ml   |
| <b>STORAGE</b>           | Keep from freezing. Store in a cool place at room temperature. |

Revision No. 0 dated February 2009

## WARNINGS

- Keep from freezing
- Shake well before and after dilution
- Do not apply on hot surfaces, in direct sunlight and when temperature is below 5°C and over 35°C
- Protect marble and metallic parts during application
- Clean the tools with water immediately after use
- Store in a dry place away from sunlight

## PAINT SYSTEM

Apply over dry and sound surfaces, removing all dust.

**New walls:** After plaster curing (30/40 days) apply one coat of PERFORMA FONDO.

**Unpainted degraded walls:** clean carefully with a wire brush; clean with low pressure washer and let the surface dry. Apply one coat of PERFORMA FONDO.

### SPECIFICATION ITEM:

#### PERFORMA FONDO

Alkali resistant consolidating primer, anti-saltpetre, highly penetrating, based on acrylic-siloxane resins in aqueous micro-emulsion.

Specific gravity: 1.010 ± 0.01 Kg/l

Spread rate: 5 m<sup>2</sup>/l per coat on civil plaster

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.