

PROFESSIONAL LINE

PERFORMA LAMATO

Quartz coating
with high permeability

CODE 24-...


DESCRIPTION AND USE

Interior and exterior quartz coating with faceted grains, supplied in medium or fine (Riviera type) grain.

The Riviera type, aesthetically nice, can be used in several and particular interior spaces. Its excellent water steam permeability and low water absorption allow to obtain a high breathable and filling finish.

Aspect of the dry film: rustic flat

APPLICATION DATA

2 h
DRY TO
TOUCH**2,9Kg/m²**
SPREAD RATE
Medium grain**2Kg/m²**
SPREAD RATE
Fine grain
(Riviera type)To smooth

Stainless steel
trowelPLANING

Plastic trowel

TECHNICAL DATA

COMPOSITION	based on acrylic-siloxane copolymers in water dispersion, resistant pigments and quartz with calibrated granulometry
SPECIFIC GRAVITY	1.870±0.030 g/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	71,25%
V.O.C.	< 40 g/L
AVERAGE VISCOSITY	Dense paste
FINENESS OF GRIND	1.8/2,5 m/m
COLOUR	White – Rivestimenti Plastici colour card – Selezione Architettura
PACKAGING	Kg 25 net weight
STORAGE	Keep from freezing. Store in a cool place at room temperature.

WARNINGS

Revision No. 0 dated February 2009

- Keep from freezing
- Do not apply on hot surfaces, in direct sunlight and when temperature is below 5°C
- Protect from rain in the days following the application
- Clean the tools with water immediately after use
- Store in a dry place away from sunlight

PAINT SYSTEM

- **New walls**
After 30-40 days curing apply one brush coat of Performa Fondo and one the coat of Performa Finitura colored as the finish. Wait at least 12 hours before applying Performa Lamato.
- **Walls to repaint**
 - Unpainted degraded walls:** brush carefully with a wire brush and clean with low pressure drinking water; let the surface dry. Apply one brush coat of Performa Fondo and one coat of Performa Finitura colored as the finish. Wait at least 12 hours and apply Performa Lamato.
 - **Walls with old paints and loose plaster:** completely remove all loose areas; brush carefully with a wire brush and clean with low pressure drinking water; let the surface dry. Restore all removed areas with hydraulic mortar or ready-mix. Let cure for at least 10 days. Apply one brush coat of Fissativo Acrilico Pigmentato colored as the finish only over the restored areas and coat over the whole surface (or of Performa Finitura). Wait at least 12 hours and apply Performa Lamato.
 - **Walls with old paints in good conditions:** Clean with water or low pressure washer; let the surface dry. Apply one coat of Performa Finitura colored as the finish. After 12 hours apply Performa Lamato.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.