PROFESSIONAL LINE

PITTURA ACRILICA

Interior and exterior satin acrylic water-based paint

CODE 08-500

DESCRIPTION AND USE

Interior and exterior acrylic water-based paint charcterized by high coverage, bright white, adherence and cleanability. Its excellent brushability, filling properties and expansion provide high quality lacquer finish for interiors. Aspect of the dry film: satin

APPLICATION DATA



TECHNICAL DATA

COMPOSITION	Based on light-resistant pigments and acrylic
	copolymers modified in water dispersion
SPECIFIC GRAVITY	1.380±0.050 g/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	36%
AVERAGE VISCOSITY	(Brookfield rot. No. 5 at 2rpm at 21℃): 500 Poises
FILM THICKNESS	Dry: 40 – Wet: 125 on two coats (µm)
FINENESS OF GRIND	15 microns
COLOURS	White
PACKAGING	14000 ml – 4000 ml
STORAGE	Keep from freezing. Store in a dry, cool place with
	adequate ventilation.





WARNINGS

- Keep from freezing
- Clean the tools with water immediatley after use
- Store in a dry place away from sunlight

PAINT SYSTEM:

Surface must be clean and dry.

- **New walls:** apply one brush coat of Supernovità. Wait at least 4 hours and apply two coats of Pittura Acrilica.
- Walls already painted:
- With washable water-based paints: fill holes and imperfections with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità only over patched areas. After at least 4 hours apply two coats of Pittura Acrilica.
- With distemper, lime paint or chalky paint: fill holes and imperfections with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità over the whole surface. After at least 4 hours apply two coats of Pittura Acrilica.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.