

CLASSIC LINE

PIÚ FRESCO

Washable water-based paint

CODE 08-600

DESCRIPTION AND USE

Washable water paint; easy to apply and washing resistant.

It is particularly suitable to protect and decorate interiors, providing an excellent matte finish on surfaces.

Aspect of the dry film: flat

APPLICATION DATA

1h DRY FOR TOUCHING min 4h
TO
RECOVER

8 m²/l 2 COATS SHAVE WALL







TECHNICAL DATA

TECHNICAL DATA	
COMPOSITION	Based on acrylic copolymers in water
	dispersion, titanium dioxide, selected charges
	and hydro-repellent extenders
SPECIFIC GRAVITY	1.500 ± 0.030 Kg/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	38%
V.O.C	< 30 g/L
AVERAGE VISCOSITY	(Brookfield rot. no.4 at 2rpm at 21℃): 400 Poises
FILM THICKNESS	Dry: 40 – Wet: 125 on two coats (µm)
FINENESS OF GRIND	30 microns
COLOURS	White – TINGO – Selezione Interni
PACKAGING	
STORAGE	Keep from freezing. Store in a cool, dry place with
	adequate ventilation.

Revision No. 0 dated February 2009





APPLICATION GUIDE

Surface must be clean and dry.

New walls: apply one brush coat of Supernovità. Wait at least 4 hours and apply two coats
of Più Fesco.

Walls already painted

- With washable water paint: fill holes with plaster and sand if necessary; clean with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours and apply two coats of Più Fresco.
- With distemper, lime paint or chalking paint: fill holes with plaster and sand if necessary;
 clean the wall with a damp sponge, apply one brush coat of Supernovità over the whole surface. Wait at least 4 hours and apply two coats of Più Fresco.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.