

WATER BASED LINE

PROTETTIVO TINTE FORTI

Colorless flat protective coating

CODE

DESCRIPTION AND USE

Interior, not yellowing, colorless flat water-based protective coating; designed for superficial protection of chalking wall surfaces (see strong hues or metal effect water-based paints). Its main features are: ease of application, slight change of the starting colour, perfect expansion; It substantially increases the cleanability level of high cleanable water-based paints (after 15 days from the last application).

Aspect of the dry film: flat


APPLICATION DATA



TECHNICAL DATA

COMPOSITION	Based on acrylic polymers modified in water dispersion, transparent pigments and special additives.
SPECIFIC GRAVITY	1.020 ± 0.020 Kg/L
FLASH PONT	Not flammable
SOLIDS BY VOLUME	22%
V.O.C.	
AVERAGE VISCOSITY	25 Sec. (Ford Cup no. 4 at 21 °C)
COLOURS	Colorless
PACKAGING	1000 ml – 4000 ml







WARNINGS

- Keep from freezing
- Shake well before and during use
- Clean the tools with water immediately after use
- Store in a cool, dry place away from sunlight

APPLICATION GUIDE

Apply one brush or spray coat of product on water-based paints completely dry (wait at least 48 hours from the last application).
N.B.: the product must be applied in big quantity (see spread rate above) wetting down the surface to protect to optimize expansion and final protective result.

Orazio Brignola S.p.A. reserves the right to update the above data which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself