

PROFESSIONAL LINE




STOPInterior, non yellowing, anti-smoking
acrylic water-based paint

CODE 25-100

DESCRIPTION AND USE

Acrylic paint designed to protect against walls yellowing especially in public spaces. Odorless product, suitable for interior application.
Aspect of the dry film: satin

APPLICATION DATA

1h DRY TO TOUCH	24h RECOAT TIME	11 m²/l SPREAD RATE 2 coats		 20% v/v	 10% v/v
---------------------------	---------------------------	---	---	--	---

TECHNICAL DATA

COMPOSITION	Based on special copolymers in dispersion and selected pigments
SPECIFIC GRAVITY	1.370±0.050 g/L
FLASH POINT	Not flammable
SOLID BY VOLUME	46%
V.O.C.	< 140 g/L
AVERAGE VISCOSITY	(Cone/Plate): 2.5 Poises
FILM THICKNESS	Dry: 65 – Wet: 150 on two coats (µm)
FINENESS OF GRIND	100µm
COLOURS	White
PACKAGING	14000 ml – 4000 ml – 750 ml
STORAGE	Store in a cool, dry place with adequate ventilation at room temperature

Revision No. 0 dated February 2009

PAINT SYSTEM

- **New walls:** apply one brush coat of Supernovità. After at least 4 hours apply two coats of Stop.
- **Walls already painted:**
 - With washable water-based paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità only over patched areas. Wait at least 4 hours and apply two coats of Stop.
 - With distemper, lime paint or chalky paint: fill holes with plaster and sand if necessary; clean the wall with a damp sponge and apply one brush coat of Supernovità over the whole surface. After 4 hours apply at least two coats of Stop.

