

DECORATIVE LINE

STUCCO ANTICO FONDO

Pigmented fixative with calibrated grain



CODE 18-350

DESCRIPTION AND USE

Pigmented fixative with calibrated grain designed for the preparation of surfaces to decorate with STUCCO ANTICO "Marble Effect" or "Veneziano Effect". Easy to apply, it permeates and consolidates the surfaces to work, making the absorptions uniform without altering the breathability of the product itself. Its peculiar granulometric curve allows to obtain a perfect smoothing since the first coat of STUCCO ANTICO, optimizing the quantity of product to use even on particularly smooth surfaces.

Aspect of the dry film: matte, rough

APPLICATION DATA

1h DRY TO TOUCH	4h RE-COAT TIME	10m²/l SPREAD RATE PER COAT	 WOOL 10% v/v	
---------------------------	---------------------------	--	---	---

TECHNICAL DATA AND CHARACTERISTICS

COMPOSITION	Based on acrylic polymer modified in aqueous emulsion, titanium dioxide, charges, extenders and selected additives
SPECIFIC WEIGHT	1.480 ± 0.030 g/L
FLASHPOINT	Not flammable
SOLIDS IN VOLUME	40 %
AVERAGE VISCOSITY	(Brookfield rot. n°3 / 2 rpm a 21°C): 250 Poises
FINENESS OF GRIND (µm)	100
COLOURS	white
PACKAGING	14000 ml – 4000 ml – 1000 ml

WARNINGS:

- Keep from freezing
- Clean the tools with water after use
- Store in a dry place away from sunlight

SURFACE PREPARATION (lime, plaster, plasterboard and already painted surfaces):

Fill any imperfections (cracks, holes) or trim in case of large irregularities; if necessary, sand the surface and clean with a damp sponge;

APPLICATION:

Apply one coat of STUCCO ANTICO FONDO with a wool paint roller; after at least 4 hours, apply a second coat only over very absorbent surfaces.

Orazio Brignola S.p.A. reserves the right to update the above data which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.