

DECORATIVE LINE

STUCCO ANTICO




Interior stucco finish

CODE Marble effect: 18-200 Veneziano effect: 18-300

DESCRIPTION AND USE

Elegant Interior solventless stucco finish; it provides a natural finish, highly breathable with antibacterial action, giving incomparable charm to your rooms. STUCCO ANTICO is easy to apply and perfectly adheres to all kind of wall surfaces even previously painted.

APPLICATION DATA

1 h DRY TO TOUCH	6-8 h RECOAT TIME	0,7Kg/m² SPREAD RATE MARBLE EFFECT	1 Kg/m² SPREAD RATE VENETIAN EFFECT	 STAINLESS STEEL TROWEL	 IPVC TROWEL	 STAINLESS STEEL
----------------------------	-----------------------------	--	---	---	---	---

TECHNICAL DATA

ASPECT	Dense white paste with a slight smell
COMPOSITION	Made with cured slaked lime, inerts and selected additives.
SPECIFIC GRAVITY	1.550 +/- 0.030 Kg/L
SOLIDS BY VOLUME	55%
AVERAGE VISCOSITY	Soft paste
FLASH POINT	Not flammable
COLOURS	See colour card
TINTING	Toner (250ml): ¼ per 2 kg - 1 per 8 kg - 3 per 24 kg
PACKAGING (Kg)	2 - 8 - 24

WARNINGS:

- Keep from freezing
- Clean the tools with water after use
- Store in a dry place away from direct sunlight

SURFACE PREPARATION (lime, plaster, plasterboard, civil and already painted):

Fill imperfections (cracks and holes) or trim in case of large areas of irregularities. If necessary, sand and clean the surface with a damp sponge.

Apply one coat of STUCCO ANTICO FONDO with a wool roller; wait at least 4 hours and apply a second coat only over very absorbent surfaces.

PAINT SYSTEM - STUCCO ANTICO Marble Effect:**1st coat:**

- Smooth wall: apply "Marble Effect" with stainless steel trowel and trim until you obtain a perfectly smooth surface.
- Irregular wall: apply one or two coat of "Veneziano Effect" with stainless steel trowel and smooth down until you obtain a perfectly smooth surface; in order to avoid any imperfections, the substrate can be wet before final smoothing.
N.B: After coloring, especially with strong colours, thicken with STUCCO ANTICO ADDENSANTE - 50 ml/8 Kg and 3x50 ml/24 Kg (let cure for at least 2 hours before use)

2nd coat: after complete desiccation (at least 6 hours) apply one coat of product with a stainless steel trowel or putty knife, creating the desired decoration. The final surface must be completely smooth.

3rd coat: apply a small quantity of product by spreading and removing with a stainless steel trowel or putty knife; before complete desiccation, polish with the stainless steel trowel.

N.B.: for lighter colours, we suggest polishing the surface by using a red pvc trowel (with rounded ends) in order to avoid the typical grayness of lime. After complete desiccation (min. 24 hours) apply STUCCO ANTICO CERA if you wish to obtain a hydrorepellent surface (see technical data sheet).

PAINT SYSTEM - STUCCO ANTICO Veneziano Effect:**1st coat:**

- Smooth or irregular wall: apply one or two coats of Effetto Veneziano with stainless steel trowel and smooth down until you obtain a perfectly smooth surface; the substrate can be wet before final smoothing to avoid any imperfections.
N.B: After coloring, especially with strong colours, thicken with STUCCO ANTICO ADDENSANTE - 50 ml/8 Kg and 3x50 ml/24 Kg (let cure for at least 2 hours before use)

2nd and 3rd coat: see "Marble Effect"