

BOAT LINE

ADDITIVO ANTISDRUCCIOLO

CODE 53-698

DESCRIPTION AND USE

Additive providing superficial roughness to the finish without altering its peculiar qualities and giving nonslip properties to the surface.

TECHNICAL DATA

COMPOSITION	Based on ethylene synthetic polymers
SPECIFIC GRAVITY	0.95± 0.02 Kg/L
AVERAGE VISCOSITY	-
GRANULOMETRY	<200 µm
pH	-
FLASH POINT	-
MELTING POINT	> 110°C
SELF-IGNITION	> 300°C
STEAM TENSION	0.075 mmHg
WATER SOLUBILITY	Not miscible
PACKAGING	35 g
STORAGE	Store in a cool, dry place with adequate ventilation

INSTRUCTIONS FOR USE

Addictivate Additivo Antisdrucchiole to paint or varnish, thoroughly mix and apply one or two coats by brush or roller.

The technical data are based on a reference temperature of 20°C unless otherwise specified.

N.B. One single package contains 35 g of Additivo Antisdrucchiole to mix with a 750 ml can of paint or varnish.

SAFETY PRECAUTIONS

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the packaging.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.

If products are not used beyond our control our liability is limited to the quality of the product itself.