

SOLUTIONS LINE

**BRIGEL**

Anti rust enamel

CODE 42-2...



**DESCRIPTION AND USE**

Anti rust gloss enamel for interiors and exteriors. It stops rusting process giving the surface a more brilliant and decorative aspect. It can be applied directly on rusted surface unless it shows flaky rust. It is chromium free and unleaded.

It does not drip.

Aspect of the dry film: polish

**APPLICATION DATA**

<b>2 h</b> DRY TO TOUCH	<b>24 h</b> RECOAT TIME	<b>9 m<sup>2</sup>/l</b> SPREAD RATE	 READY TO USE	 READY TO USE
----------------------------	----------------------------	---	---	---

**TECHNICAL DATA**

<b>COMPOSITION</b>	Dissolved thixotropic alkyd resin and high resistant pigments.
<b>SPECIFIC GRAVITY</b>	1.200 ±0.020 Kg/L
<b>FLASH POINT</b>	Over 21°C
<b>SOLIDS BY VOLUME</b>	52%
<b>V.O.C.</b>	<500 g/L
<b>AVERAGE VISCOSITY</b>	(Cone/Plate at 20°C) : 6 Poises
<b>FILM THICKNESS</b>	Dry: 45 Wet: 85 (µm)
<b>FINENESS OF GRIND</b>	5 microns
<b>COLOURS</b>	See colour card
<b>PACKAGING</b>	750 ml
<b>STORAGE</b>	Keep from freezing. Store in a cool, dry place with adequate ventilation.

Revision No. 4 dated February 2009

## PAINT SYSTEM GUIDE

### See Tin

- **New iron:** degrease and apply two coats of Brigel.
- **Rusted surfaces:** remove all flaky rust and apply two coats of Brigel.
- **Already painted iron:** remove all loose scale if necessary, degrease and touch up rusted areas with Brigel; then apply one or two coats of Brigel.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.