

COTTAGE LINE

COTTAGE EFFETTO CERA

U.V. resistant, non flaking,
satin finish



CODE 12-04.

DESCRIPTION AND USE

Satin, coloured, non flaking coating based on natural wax and alkyd-urethane resins. It deeply protects wood providing water resistance. Thanks to its special UV absorbers, Cottage Effetto Cera protects wood cells against UV rays that are one of the main factors causing wood aging and graying process.

Designed for the protection and decoration of headrooms, matchboards, balconies, frames etc.
Aspect of the dry film: satin

APPLICATION DATA

3h DRY TO TOUCH	24h RECOAT TIME	11 m²/L SPREAD RATE	 READY TO USE	 READY TO USE
------------------------------	------------------------------	---	--	--

TECHNICAL DATA

COMPOSITION	Based on alkyd-urethane resins with special additives, transparent oxides and wax
SPECIFIC GRAVITY	0.880 ± 0.020 kg/L
FLASH POINT	Over 21°C
SOLIDS BY VOLUME	38%
V.O.C.	495 g/L
AVERAGE VISCOSITY	(Gardner at 21°C) : 0.6 Poises
FILM THICKNESS	Dry: 25 Wet: 65 (µm)
FINENESS OF GRIND	3 microns
COLOURS	See colour card
PACKAGING	2500 ml– 750 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation.

Revisione N°1 del febbraio/2009

PAINT SYSTEM

SEE TIN

- **New wood:** prepare the surface carefully, sand and remove all dust and dirt. When the substrate has completely dried, apply one coat of Cottage Effetto Cera thinned to 20% with Thinner no. 7. Lightly sand and after 24 hours apply two coats of undiluted Cottage Effetto Cera.
- **Already painted wood:** sand and remove all loose paint. Thoroughly clean and when the surface has completely dried, apply one or two coats of Cottage Effetto Cera.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.