

COTTAGE LINE

# COTTAGE IMPREGNANTE

Colored protective coating

CODE 12-02.



**DESCRIPTION AND USE**

Interior and exterior coating with excellent impregnation properties. It protects wood against weathering, moulds, fungi etc., highlighting its natural grain.

Non-filmogenous product, it provides protection against cracking, peeling and flaking.

Aspect of the dry film: semi-gloss

**APPLICATION DATA**

<b>18h</b> DRY TO TOUCH	<b>min 3h</b> RECOAT TIME	<b>15m<sup>2</sup></b> SPREAD TIME	 THINNER		<b>DIMMING</b>
----------------------------	------------------------------	---------------------------------------	---	--	----------------

**TECHNICAL DATA**

<b>COMPOSITION</b>	Based on urethanized oils and transparent oxides
<b>SPECIFIC GRAVITY</b>	0.830 ± 0.005 Kg/L
<b>FLASH POINT</b>	Over 21°C
<b>SOLIDS BY VOLUME</b>	20%
<b>V.O.C.</b>	< 700 g/L
<b>AVERAGE VISCOSITY</b>	0.5 Poises (Gardner at 21°C)
<b>FILM THICKNESS</b>	Dry: 10 Wet: 50 (µm)
<b>FINENESS OF GRIND</b>	2 microns
<b>COLOURS</b>	See colour card
<b>PACKAGING</b>	18000 ml – 4000 ml – 2500 ml – 750 ml
<b>STORAGE</b>	Keep from freezing. Store in a cool, dry place with adequate ventilation

Revision No. 1 dated February 2009

## **PAINT SYSTEM**

- **New wood:** thoroughly sand and clean all dust and dirt. Make sure the surface is completely dry and apply two coats of Cottage Impregnante waiting 3 hours between the two coats.
- **Wood painted with impregnating coating:** clean the surface thoroughly and apply one or two coats of Cottage Impregnante.
- **Wood already painted with enamel or varnish:** thoroughly sand down removing all traces of paint. Clean carefully and when the substrate has completely dried, apply one or two coats of Cottage Impregnante.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.  
If products are not used beyond our control our liability is limited to the quality of the product itself