

COTTAGE LINE

COTTAGE PAVIMENTI

Gloss and flat one-pack finish




CODE 12-03.

DESCRIPTION AND USE

Polyurethane one-pack finish designed to provide long-lasting protection to wood flooring. It forms a hard film resistant to trampling, cleaning agents, oils and grease.

Aspect of the dry film: gloss or satin

APPLICATION DATA

2h DRY TO TOUCH	24h RECOAT TIME	72h READY TO TRAMPLE	11 m² SPREAD RATE			
---------------------------	---------------------------	--------------------------------	--	--	--	---

TECHNICAL DATA

COMPOSITION	Based on alkyd-urethane resins
SPECIFIC GRAVITY	0.940 ± 0.050 Kg/L
FLASH POINT	Over 21°C
SOLIDS BY VOLUME	38%
V.O.C.	590 g/L
AVERAGE VISCOSITY	2.2 Poises (Gardner at 21°C)
FILM THICKNESS	Dry: 25 Wet: 65 (µm)
FINENESS OF GRIND	3 microns
COLOURS	Matte - gloss
PACKAGING	2500 ml – 750 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation

PAINT SYSTEM

- **Unpainted wood flooring:** prepare the surface carefully, sand down and clean off dust and dirt. Make sure the surface is completely dry.
Apply at least two coats of Cottage Pavimenti, waiting 24 hours between the two coats.
- **Painted wood flooring:** sand down removing old paint. Clean thoroughly and make sure the surface is completely dry. Apply one or two coats of Cottage Pavimenti.
- **Wax-finished wood flooring:** in order to achieve perfect adherence, make sure the floor is thoroughly sanded before applying Cottage Pavimenti .

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.
If products are not used beyond our control our liability is limited to the quality of the product itself