

COTTAGE LINE

COTTAGE VERNICE

One-pack color, gloss and satin varnish

CODE 12-00.

DESCRIPTION AND USE

One pack polyurethane varnish, with filling properties and high resistance, highlighting wood natural grain. Designed for the protection and decoration of all kinds of woods for both interiors and exteriors (attics, balconies, matchboarding, frames etc.).

Aspect of the dry film: gloss or satin, colour or colorless

APPLICATION DATA

2h DRY TO TOUCH	12h RECOAT TIME	12 m²/l SPREAD TIME	 READY TO USE	 READY TO USE
---------------------------	---------------------------	--	--	--

TECHNICAL DATA

COMPOSITION	Based on alkyd-urethane resins and transparent oxides
SPECIFIC GRAVITY	0.910 ± 0.020 Kg/l
FLASH POINT	Over 21°C
SOLIDS BY VOLUME	45%
V.O.C.	Max. 520 g/lL
AVERAGE VISCOSITY	1.4 Poises (Gardner at 21°C)
FILM THICKNESS	Dry: 25 Wet: 55 (µm)
FINENESS OF GRIND	2 microns
COLOURS	See colour card
PACKAGING	2500 ml – 750 ml – 375 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation.

Revisione N°4 del febbraio/2009

PAINT SYSTEM

- **New wood:** thoroughly prepare the surface, sand and remove all dust and dirt. Make sure the surface is completely dry.
If you work on exterior surfaces, first you have to apply one coat of Cottage Impregnante to achieve complete protection. Apply at least 2 coats of Cottage Vernice.
- **Painted wood:** thoroughly sand and remove all loose paint. Clean carefully and make sure the surface is completely dry. Apply one or two coats of Cottage Vernice.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.
If products are not used beyond our control our liability is limited to the quality of the product itself