COTTAGE LINE

FILM U.V. resistant flexible varnish CODE 15-4..

DESCRIPTION AND USE

RIGNO

High-quality, U.V. resistant, flexible one-pack varnish; the flexibility of the film, stable in time and even at quite low temperatures (0°C), easy adapts to the natural movement of wood, keeping non flakying properties in all types of working conditions (civil, industrial, marine).

Thanks to its peculiar ease of application and excellent expansion you will obtain perfect final results.

Aspect of the dry film: colorless, gloss or matte

APPLICATION DATA



TECHNICAL DATA

COMPOSITION	Long oil alkyd resins, waxes and special U.V.
	additives.
SPECIFIC GRAVITY	0.900 ± 0.020 Kg/L
FLASH POINT	Over 21℃
SOLIDS BY VOLUME	54%
V.O.C.	485 g/L
AVERAGE VISCOSITY	(Ford no. 8 Cup at 21℃): 30 Sec
FILM THICKNESS	Dry: 40 Wet: 75 (per coat)
COLOURS	See colour card
PACKAGING	2500 ml – 750 ml – 375 ml





WARNINGS

- Do not apply in direct sunlight
- Thin and clean working tools with Thinner no. (Universal Thinner)
- Store in a dry place away from direct sunlight.

PAINT SYSTEM

• **New wood:** apply one or two coats of colour or colorless COTTAGE IMPREGNANTE; apply one coat of gloss or matte FILM. Wait at least 18 hours then lightly sand with 320 grit wet sandpaper; clean the surface with a damp sponge and let it dry. Apply a second coat of gloss or matte FILM. We suggest applying a third coat to improve its protective ability and the final aspect of the finish.

• Painted wood:

Open-pore finish: remove all loose paint; first sand with 120 grit wet sandpaper and subsequently with 320 grit wet sandpaper.

Clean with a damp sponge, let dry and follow New wood guidelines.

Closed-pore finish: in presence of adherent old paint, sand with grit 320 wet sandpaper, clean witha damp sponge and let dry. Apply two coats of gloss or matte FILM.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself