

COTTAGE LINE

IMPREGNANTE ALL'ACQUA

Penetrating acrylic protective coating Coloured and colourless CODE 12-72.

DESCRIPTION AND USE

Interior and exterior water-based wood stain; it is absorbed into wood fibers, highlithing its natural grain, without creating any superficial peel and protecting wood from moulds and fungi. When finished outside, colored type is recommended.

Aspect of the dry film: semi gloss

APPLICATION DATA

30 min DRY TO TOUCH











DIMMING

TECHNICAL DATA

COMPOSITION	Based on acrylic copolymers in water dispersion, transparent oxides and special additives.
SPECIFIC GRAVITY	1.000 ± 0.030 kg/L
FLASH POINT	Not flammable
SOLIDS BY VOLUME	18%
V.O.C.	<130 g/L
AVERAGE VISCOSITY	15 Sec (Ford Cup No. 4 at 21℃)
COLOURS	See colour card
PACKAGING	2500 ml – 750 ml
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation.





PAINT SYSTEM

Shake well before use.

Do not apply below 5° and over 35° .

Do not apply on wet wood.

Do not apply outside when rain is imminent.

It can be topcoated with all water and solvent based enamels or varnishes; make sure it has completely dried.

It can be applied on surfaces already treated with solvent-based impregnating coating. Clean the tools with water after use.

- **New wood:** thoroughly prepare the surface, sand and remove all dust, grease, wax and silicones. For a better and complete protection, we suggest applying one or two coats of Impregnante all'acqua.
- Wood painted with wood stain: thoroughly clean the surface and lightly sand if necessary; apply one ore more coats of Impregnante all'acqua.
- Wood painted with enamels or varnish: remove or scrape off all old; sand down, remove all dust and follow New wood guidelines.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself