

PROFESSIONAL LINE

LAMATO ACRILICO

High build masonry coating

CODE 22-...

DESCRIPTION AND USE

Interior and exterior Quartz Coating with faceted grains available in medium and fine grained types. The fine grained one (Riviera type), aesthetically nice, is frequently used for particular interior design.

Its high flexibility allows colorfastness and durability also over microcracked surfaces subject to small structural movement.

Aspect of the dry film: rustic flat

APPLICATION DATA

2-3 h

DRY TO
TOUCH

2,9kg/m²

SPREAD RATE
Medium grane

2 kg/m²

SPREAD RATE
Fine grain
(Riviera type)

TO SMOOTH



Stainless steel
trowel



SPOT FACED
Plastic trowel

Revision No. 2 dated February 2009

TECHNICAL DATA

| | |
|--------------------------|--|
| COMPOSITION | Based on styrol-acrylic copolymers in water-dispersion, resistant pigments and calibrated grain quartz |
| SPECIFIC GRAVITY | 1.870±0.030 kg/L |
| FLASH POINT | Not flammable |
| SOLIDS BY VOLUME | 71.25% |
| V.O.C. | < 40 g/L |
| AVERAGE VISCOSITY | Solid paste |
| FILM THICKNESS | Dry: 1200 – Wet: 1650 (µm) |
| FINENESS OF GRIND | 1.8/2,5 m/m |
| COLOURS | White – Plastic coating (rivestimenti plastici) colour card – Selezione Architettura |
| PACKAGING | Kg 25 net weight |
| STORAGE | Keep from freezing. Store in a dry place at room temperature. |

WARNINGS:

- Keep from freezing
- Do not apply in direct sunlight or when temperature is below 5°C.
- Protect from rain in the days following the application.
- Thoroughly clean the tools with water after use .
- Store in a dry place away from sunlight.

PAINT SYSTEM

- **New walls**
Let the surface dry for 30-40 days then apply one brush coat of Fissativo Acrilico Pigmentato (of the same colour of the finish). Wait at least 12 hours and apply Lamato Acrilico.
- **Walls to repaint**
 - **Degraded walls without old paint:** thoroughly brush with a wire brush. Clean with low pressure drinking water. Let the surface dry completely. Apply one brush coat of Isoflex or Fissativo Acrilico Pigmentato. Wait 12 hours and apply Lamato Acrilico.
 - **Walls with old paint and loose plaster:** completely remove all loose paint and plaster; thoroughly brush with a wire brush. Clean with low pressure drinking water; let the surface dry completely. Touch up removed areas with hydraulic mortar or ready-mix concrete. Let the surface dry for at least 10 days. Apply one brush coat of Fissativo Acrilico only on restored areas and one coat of Quarzo (of the same colour of the finish) over the whole surface. Wait at least 12 hours and apply Lamato Acrilico.
 - **Walls with old paint in good conditions:** Clean with water or water blaster. Let the surface dry completely. Apply one coat of Quarzo (of the same colour of the finish); wait at least 12 hours and apply Lamato Acrilico.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.