

**BOAT LINE** 

# **PAINT REMOVER**


Water-based paint stripper

CODE 10-067

## **DESCRIPTION AND USE**

Paint Remover is a water-based varnish remover suitable for antifouling, enamel, primers and antirust coatings. It doesn't damage the gelcoat and epoxy based products. Thanks to its characteristics, it can also be used in rooms with low ventilation.

# **APPLICATION DATA**



## **TECHNICAL DATA**

COMPOSITION	Based on pyrrolidone, Chloromethane and Sodium hydroxide free
SPECIFIC GRAVITY	1.02±0.05 Kg/L
AVERAGE VISCOSITY	(Brookfield RVT 2 rpm spindle no. 6 at 21°C): 105 Pois e
FILM THICKNESS	Wet: 1 mm abt
FINENESS OF GRIND	-
SOLIDS BY VOLUME	25±3%
V.O.C. % BY WEIGHT	42.30
FLASH POINT	>55°C
MIXING RATIO BY VOLUME	-
POT-LIFE	-
COLOURS	Light yellow
PACKAGING	ml 1000
STORAGE	Keep from freezing. Store in a cool, dry place with adequate ventilation





#### PAINT SYSTEM

Apply one 1 mm thick coat over the whole surface to paint, let it work for 1 up to 12 hours, depending on the quantity and type of paint to strip. Remove the paint with a scraper or a putty knife and clean with large amounts of water. The good result will be determined by the thickness of the paint stripper applied over the surface to treat.

#### **CONDITIONS FOR APPLICATION**

Apply at a temperature between 5℃ and 35℃. Do not store at a temperature below 4 ℃.

## INSTRUCTIONS FOR USE

Stir well before use.

The technical data are based on a a reference temperature of 20°C unless otherwise specified and refer to the product undiluted and ready-to-use.

#### SAFETY PRECAUTIONS

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the packaging.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.