

CLASSIC LINE

# PROTEXITE


Interior and exterior finish  
and flat primer

CODE 11-201

**DESCRIPTION AND USE**

Alkyd-based primer with high coverage and filling properties. Easy to sand and providing a good adhesion to the substrate it is normally used for the preparation of wood to synthetic enamel applications. It can also be used as filling primer for iron handiworks.  
Aspect of the dry film: flat

**APPLICATION DATA**

<b>1.5h</b> DRY TO TOUCH	<b>18 h</b> RECOAT TIME	<b>9 m<sup>2</sup>/l</b> SPREAD RATE	 READY TO USE
-----------------------------	----------------------------	---	---

**TECHNICAL DATA**

<b>COMPOSITION</b>	Based on alkyd resins, titanium dioxide, white pigments and extenders
<b>SPECIFIC GRAVITY</b>	1.550 ± 0.030 Kg/l
<b>FLASH POINT</b>	Over 21°C
<b>SOLIDS BY VOLUME</b>	50%
<b>AVERAGE VISCOSITY</b>	22 Sec (Ford Cup no. 4 at 21°C)
<b>FILM THICKNESS</b>	Dry: 40 – Wet: 100
<b>FINENESS OF GRIND</b>	25 microns
<b>COLURS</b>	Matte white
<b>PACKAGING</b>	2500 ml – 500 ml – 250 ml
<b>STORAGE</b>	Keep from freezing. Store in a cool, dry place with adequate ventilation.

## **APPLICATION GUIDE**

### **Surface preparation:**

Apply one coat of thinned product, following the instructions given above. Fill holes with Stucco a Spatola. After 24 hours sand and apply a second coat of Protexite. Finally apply the finish desired.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.  
If products are not used beyond our control our liability is limited to the quality of the product itself