

**BOAT LINE** 

# **RAVILAKK**

Glossy varnish

**CODE 15-700** 

# **DESCRIPTION AND USE**

Glossy varnish made with China wood oil and synthetic amber. It has good water and weathering resistance. Quick drying. For use above the waterline, on interior and exterior wooden surfaces. Do not use over old lacquer finish.

# **APPLICATION DATA**

6h DRYTO TOUCH

24h HARD DRY min 24h RECOAT TIME

17m/l THEORETICAL COVERAGE 12m/l PRACTICAL COVERAGE





# **TECHNICAL DATA**

COMPOSITION	Based on China wood oil and synthetic amber
SPECIFIC GRAVITY	0.90±0.05 Kg/L
AVERAGE VISCOSITY	(Ford Cup no. 4 at 21℃): 147"
FILM THICKNESS	Dry: 35 – Wet: 70 (μm)
FINENESS OF GRIND	-
SOLIDS BY VOLUME	51±3%
V.O.C. % BY WEIGHT	43.33
FLASH POINT	>21℃
MIXING RATIO BY VOLUME	-
POT-LIFE	-
COLOURS	Amber
PACKAGING	ml 2500 – ml 750
STORAGE	Store in a cool, dry place with adequate ventilation



#### **PAINT SYSTEM**

#### New wood

**Surface preparation:** Sand and dust. Since foreign matters such as glues, grease, etc. affect priming and cause adhesion problems, they must be completely removed. Make sure the timber is dry before starting the application.

Apply one coat of Ravilakk diluted with 15% thinner N° 7. If the substrate has a strong absorption, apply a second coat of product diluted with 10% Thinner N° 7. Apply two or three coats of undiluted Ravilakk. For an excellent finish we suggest sanding with fine abrasive paper between coats.

**N.B.** If you wish to prime wood refer to the primers of the Cottage Line.

#### Wood (maintainance)

Surface preparation: Thoroughly sand the surface.

Apply two coats of undiluted Ravilakk.

## **CONDITIONS FOR APPLICATION**

Apply at a temperature between  $5^{\circ}$ C and  $35^{\circ}$ C. Do not apply when the surface temperature is below  $3^{\circ}$ C at dew point.

## **INSTRUCTIONS FOR USE**

Stir well before use.

The technical data are based on a a reference temperature of 20℃ unless otherwise specified and refer to the product undiluted and ready-to-use.

The product is ready to use.

## **SAFETY PRECAUTIONS**

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the package label.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.

60 Revisione N°0 del 19/01/2009