

BOAT LINE

THINNER N° 10

Polyurethane thinner

CODE 10-110

DESCRIPTION AND USE

Blend of aromatic hydrocarbons and acetates designed for use with most two-pack polyurethane coatings. It can be used to degrease all kinds of surfaces prior to priming, or to clean working tools after use.

TECHNICAL DATA

COMPOSITION	Blend of butyl ester xylenes and glycol ether acetates
SPECIFIC GRAVITY	0.91± 0.02 Kg/L
FLASH POINT	35±2°C
MOLECULAR WEIGHT	122 (calculated)
MELTING POINT	-65±2°C (air=1)
SELF-IGNITION	384±2°C
LOWER EXPLOSIVE LIMIT	1.5 (% vol/vol)
UPPER EXPLOSIVE LIMIT	6.8 (% vol/vol)
STEAM TENSION	15 mm (Hg at 20°C)
STEAM DENSITY	4.2 (air=1)
WATER-IN-SOLVENT	1.96 (g/L at 20°C)
SOLVENT-IN-WATER	10.10 (g/l at 20°C)
TLV-TWA	109 ppm
TLV-TWA	541 mg/m ³
PACKAGING	1000 ml
STORAGE	Store in a cool, dry place with adequate ventilation

SAFETY PRECAUTIONS

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the package label.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only. If products are not used beyond our control our liability is limited to the quality of the product itself.