

BOAT LINE

**THINNER N°17**

Epoxy thinner

CODE 10-175

**DESCRIPTION AND USE**

Blend of aromatic hydrocarbons, glycol ethers and acetates designed for use with most two-pack epoxy coatings. It can be used to degrease all kinds of surfaces prior to priming or to clean working tools after use.

**TECHNICAL DATA**

<b>COMPOSITION</b>	Blend of petrol derivatives, ethers and glycol ether acetates
<b>SPECIFIC GRAVITY</b>	0.89± 0.02 Kg/L
<b>FLASH POINT</b>	361±2°C
<b>MOLECULAR WEIGHT</b>	109 (calculated)
<b>MELTING POINT</b>	-68±2°C (air=1)
<b>SELF-IGNITION</b>	398±2°C
<b>LOWER EXPLOSIVE LIMIT</b>	1.3 (% vol/vol)
<b>UPPER EXPLOSIVE LIMIT</b>	8.5 (% vol/vol)
<b>STEAM TENSION</b>	21 mm (Hg at 20°C)
<b>STEAM DENSITY</b>	3.7 (air=1)
<b>WATER-IN-SOLVENT</b>	28.40 (g/L at 20°C)
<b>SOLVENT-IN-WATER</b>	30.42 (g/L at 20°C)
<b>TLV-TWA</b>	86 ppm
<b>TLV-TWA</b>	375 mg/m <sup>3</sup>
<b>PACKAGING</b>	5000 – 1000 ml
<b>STORAGE</b>	Store in a dry, cool place with adequate ventilation

**SAFETY PRECAUTIONS**

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the package label.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.

If products are not used beyond our control our liability is limited to the quality of the product itself.