

BOAT LINE

THINNER N°7

Universal synthetic thinner

CODE 10-161

DESCRIPTION AND USE

Blend of aromatic and aliphatic hydrocarbons designed for use with most one-pack coatings. It can be used to degrease all kinds of surfaces prior to priming or to clean working tools after use.

TECHNICAL DATA

COMPOSITION	Based on blends of mineral turpentine, naphta solvents (petroleum and esters)
SPECIFIC WEIGHT	0.89± 0.02 Kg/L
FLASH POINT	41±2°C
MOLECULAR WEIGHT	122 (calculated)
MELTING POINT	-58±2°C (air=1)
SELF-IGNITION	443±2°C
LOWER EXPLOSIVE LIMIT	1.1 (% vol/vol)
UPPER EXPLOSIVE LIMIT	6.4 (% vol/vol)
STEAM TENSION	15 mm (Hg at 20°C)
STEAM DENSITY	4.2 (air=1)
SOLVENT-IN-WATER	0.40 (g/L at 20°C)
WATER-IN-SOLVENT	2.41 (g/L at 20°C)
TLV-TWA	64 ppm
TLV-TWA	318 mg/m ³
PACKAGING	5000 – 1000 ml
STORAGE	Store in a cool, dry place with adequate ventilation

SAFETY PRECAUTIONS

Wear appropriate personal protective equipment; use safety equipment; use with adequate ventilation. For additional safety information, please see the package label.

This version supersedes any prior version.

Orazio Brignola S.p.A. reserves the right to update the above data, which are given for information only.

If products are not used beyond our control our liability is limited to the quality of the product itself.